

Certificate of compliance

Applicant:

JIANGSU GOODWE POWER SUPPLY TECHNOLOGY CO., LTD No.90 ZiJin Rd., New District. Suzhou, 215011 China

Product: Photovoltaic (PV) inverter

Model:

GW25K-MT GW30K-MT

GW36K-MT

Inverter for three-phase parallel connection to the public grid. The network monitoring and disconnection device is an integral part of the above-mentioned model.

Applied rules and standards:

EN 50549-1:2019

Requirements for parallel connection of installations with distribution networks - Part 1: Connection to an LV distribution network -Production of installations up to and including Type B

- 4.4 Normal operating range
- 4.5 Immunity to disturbances
- 4.6 Active response to frequency deviation
- 4.7 Power response to voltage variations and voltage changes 4.8 EMC and power quality
- 4.9 Interface protection
- 4.10 Connection and starting to generate electrical power
- 4.11 Ceasing and reduction of active power on set point
- 4.12 Remote information exchange

4.13 Requirements regarding single fault tolerance of interface protection system and interface switch

EN 50438:2013

Requirements for micro-generating plants to be connected in parallel with public low-voltage distribution networks

DIN V VDE V 0126-1-1:2006 (4.1 Functional safety)

Automatic disconnection device between a generator and the public low-voltage grid

Commission Regulation (EU) 2016/631 of 14 April 2016

Establishing a network code on requirements for grid connection of generators (NC RFG). Type approval for generation units to use in Type A and Type B plants.

At the time of issue of this certificate, the safety concept of an aforementioned representative product corresponds to the valid safety specifications for the specified use in accordance with regulations.



BUREAU VERITAS Consumer Products Services Germany GmbH cps-hamburg@de.bureauveritas.com www.bureauveritas.de/cps



Appendix

Extract from test report according to EN 50549-1			No. PV190409N037-R1
Type Approval and declaration 2016/631 of 14 April 2016	on of compliance with the requ	irements of EN 50549-1 and Co	mmission Regulation (EU)
Manufacturer / applicant	JIANGSU GOODWE POWER SUPPLY TECHNOLOGY CO., LTD		
	No.90 ZiJin Rd., New District,		
	Suzhou, 215011		
	China		
Micro-generator Type	Photovoltaic inverter		
	GW25K-MT	GW30K-MT	GW36K-MT
MPP DC voltage range [V]	200~950		
Input DC voltage range [V]	Max. 1100		
Input DC current [A]	30/30/30		
Output AC voltage [V]	3/N/PE~400 or 3/PE~400, 50Hz		
Output AC current [A]	40	48	53,3
Output power [VA]	25	30	36/33*
Firmware version	Beginning with V1.01.01.01		
	·		
Description of the structure of	of the power generation unit:		
The power generation unit is e between DC input and AC output	equipped with a PV and line-side out. Output switch-off is performe		ion unit has no galvanic isolation ad on two series-connected relays network in case of error.
Note:			
The settings of the interface pro	otection are password protected a	adjustable.	
In case the above stated gener adjusted according to the manu		rotection device, the protection s	ettings of the inverters are to be

The above stated generators are tested according to the requirements in the EN 50549-1:2019 Commission Regulation (EU) 2016/631 of 14 April 2016. Any modification that affects the stated tests must be named by the manufacturer/supplier of the product to ensure that the product meets all requirements.